



SOLARFOR



SOLÁRNÍ SYSTÉM CSST "GeminiPLUS" "GeminiPLUS" CSST SOLAR SYSTEM

OHEBNÉ ZVLNĚNÉ NEREZOVÉ TRUBKY PRO SOLÁR "GEMINIplus"

Nerezové dvojité potrubí "GEMINIplus" z nerezavějící oceli **1.4301 (AISI 304)** (vhodné pro styk s pitnou vodou) opatřené izolací EPDM tloušťky 13 mm s integrovaným kabelem, použití pro solární systémy.




"GEMINIplus" SOLAR DOUBLE CSST TUBES

"GEMINIplus" double pliable corrugated CSST tubing, in **1.4301 (AISI 304)** austenitic stainless steel (suitable for drinking water), with coating in expanded EPDM 13 mm thick for thermal solar plants and sensor cable.

KÓD – EMTOP CODE – PSP	ČÁROVÝ KÓD BAR CODE	DN	ZÁVIT CONN. THREAD	DÉLKA METRES	Kč / METR METRE	Kč / BALENÍ PACK
1014033 (F0025-00600)		15	3/4"	25	690,00	17.250
1014034 (F0050-00601)				50	690,00	34.500
1014035 (F0100-00602)				100	690,00	69.000
1014043 (F0025-00603)		20	1"	25	820,00	20.500
1014044 (F0050-00604)				50	820,00	41.000
1014045 (F0100-00605)				100	820,00	82.000

SOLÁRNÍ SYSTÉM CSST "GEMINIplus" "GEMINIplus" CSST SOLAR SYSTEM



Pro solární systémy jsou k dispozici **dvojité zvlněné ohebné trubky CSST "GEMINIplus"** s kabelem pro čidlo.

Trubky "GEMINIplus" jsou vyrobeny z austenitické nerezové oceli **1.4301 (AISI 304)** (vhodné pro styk s pitnou vodou), jsou opatřené izolací EPDM tloušťky 13 mm, určeny pro solární tepelné systémy. Připojit lze buď pomocí převlečných matic a vsuvek s dosedací plochou (nutná výroba pertlu) nebo přechodů s O-kroužky (bez nutnosti výroby pertlu).

For the thermal solar plants also the **"GEMINIplus" corrugated CSST tubing double with sensor cable** are available.

The "GEMINIplus" tubing are in **1.4301 (AISI 304)** austenitic stainless steel (suitable for drinking water), with coating in expanded EPDM 13 mm thick for thermal solar plants and can be connected using the fittings for tubes to be flanged (nuts, male and female fittings, tees, etc.) or connection fittings with O-ring.