

SOLÁRNY SYSTÉM CSST "GeminiPLUS" "GeminiPLUS" CSST SOLAR SYSTEM

VLNITÉ RÚRKY Z NEHRDZAVEJÚCEJ OCELE CSST NA SOLÁR "GEMINIplus"

"GEMINIplus" dve vlnité rúrk s austenitickej nehrdzavejúcej oceli **1.4301 (AISI 304)** s 13 mm hrubou EPDM izoláciou pre solárne tepelné systémy a kábel sondy.




"GEMINIplus" SOLAR DOUBLE CSST TUBES

"GEMINIplus" double pliable corrugated CSST tubing, in **1.4301 (AISI 304)** austenitic stainless steel (suitable for drinking water), with coating in expanded EPDM 13 mm thick for thermal solar plants and sensor cable.

KÓD – EMTOP CODE – PSP	ČIAROVÝ KÓD BAR CODE	DN	ZÁVIT CONN. THREAD	DĹŽKA METRES	€/ m	€/ BALENIE €/ ROLL
1014033 (F0025-00600)		15	3/4"	25	26,40	660,00
1014034 (F0050-00601)				50	26,40	1320,00
1014035 (F0100-00602)				100	26,40	2640,00
1014043 (F0025-00603)		20	1"	25	31,20	780,00
1014044 (F0050-00604)				50	31,20	1560,00
1014045 (F0100-00605)				100	31,20	3120,00

SOLÁRNY SYSTÉM CSST "GeminiPLUS" "GeminiPLUS" CSST SOLAR SYSTEM



Pre solárne systémy je k dispozícii aj dvojica vlnitých rúrok CSST "GEMINIplus" s káblom na sondu. Rúry "GEMINIplus" sú vyrobené z austenitickej nehrdzavejúcej oceli **1.4301 (AISI 304)** s 13 mm hrubou izoláciou EPDM na solárne tepelné systémy. Môžu byť spájané pomocou matice a vsuvky (nutná výroba príruby), alebo fittingov s O-krúžkami (bez výroby príruby).

For the thermal solar plants also the "GEMINIplus" corrugated CSST tubing double with sensor cable are available. The "GEMINIplus" tubing are in **1.4301 (AISI 304)** austenitic stainless steel (suitable for drinking water), with coating in expanded EPDM 13 mm thick for thermal solar plants and can be connected using the fittings for tubes to be flanged (nuts, male and female fittings, tees, etc.) or connection fittings with O-ring.